



RICINASH

Renewable Materials Private Limited
Ways of Oleochemistry

Product Data Sheet - rev.01/04/26

RiFine-Lx_{3/6/9}

Polyglycerol Laurate (PGL 3/6/9)

Description

RiFine-Lx_{3/6/9} is made from renewable raw materials derived from plant origin. It has versatile properties that improve a product's chemistry/processability.

Characteristic Values*

Properties	Units	AOCS Test Method	RiFine-Lx ₃ PG3L	RiFine-Lx ₆ PG6L	RiFine-Lx ₉ PG9L
Physical:					
Appearance	@ 25°C	Visual	White Waxy solid	Amber Liquid	Amber Liquid
Clarity molten form	Gardner Tube	Visual	Little Hazy	Clear	Clear
Color molten form	Gardner Scale	Visual	3 Max	8 Max	12G+
Moisture	%	Ca 2c-25	1 Max	1 Max	1 max
Viscosity bubble secs	@ 25°C Gardner Tube	Cc-1-25	39 +/- 3	25 +/- 3	114 +/- 5
Emulsion. 5% disp. in hot water w/w	@ 25°C	Visual	Stable	Stable	Stable
Chemical:					
Acid Value	mg KOH/g	Cd 3d-63	3 Max	6 Max	6 Max
Saponification. Value	mg KOH/g	Cd 3-25	220-230	165-185	50-60
Iodine Value	cg I ₂ /g	Tg 1-64	3 Max	3 Max	2 Max
Hydroxyl Value	mg KOH/g	Cd 13-60	350-380	255-355	490-510
HLB	@ 25°C	Std. Formula	4-5	5-7	11-13

*Slight variations in the characteristic values stated are possible due to production made out of natural raw materials but it shall have no influence on its application functionalities.

Packing: In Barrels (net wt. 200 kgs)

Shelf Life / Storage: Shelf life is 12 months from manufacturing date when stored in a cool place (< 35°C), in tightly closed packaging, protected from dust, heat, & moisture.

The information given in this leaflet is based on our own research & development work and is correct to the best of our knowledge. We recommend that the actual users should conduct their own tests to determine the suitability of our products for their end use. Users should refer to the MSDS and other relevant data for safe handling. Our Company shall not be responsible for any loss, injury, damage, and patent or law infringement, resulting from the use of this information.